



STANG INDUSTRIES

FIRE FORCE 11 PORTABLE HIGH FLOW TRAILER



Shown with Stang Monitor

Stang Industries

WWW.stangindustries.com

951-479-9810

Product Description:

The Fire-Force 11 is a trailer-mounted mobile monitor capable of nominally delivering 10000 GPM (37,900 LPM) of water or foam solution. The Fire- Force 11 has a discharge reach exceeding 500 ft (152 Meters - under nominal flow conditions) when supplied with 160 psi (1100 kPa) at the trailer's inlet.

Monitor and Nozzle:

Water is supplied through a single 10" (254 mm) Multi-lug connection located at the rear of the trailer. Optionally, the Multi-lug connection can be replaced with other connection adaptors to match the user's hose type (Storz, groove, etc.). A 10" (254 mm) stainless steel waterway is integrated into the trailer body, feeding the 8" (203 mm) stainless steel monitor. The monitor has an uninterrupted 360° rotational range and has an elevation range from -5° to 90°. The monitor is manually controlled using handwheels for rotation and elevation. Optionally, the monitor can be equipped with electric controls - either tethered or wireless. The monitor also includes a pressure gauge to ensure sufficient water supply pressure.

Trailer:

The Fire-Force 11 is integrated into a standard over-the-road trailer. The height-adjustable hitch can be either pintle-style or ball-style to accommodate any standard towing vehicle. The trailer is equipped with a standard US-DOT vehicle lighting package. Electric brakes are provided to facilitate towing, and a runaway brake is included to automatically stop the trailer in the event of vehicle separation.

Adjustable crank-style jacks are located on the tongue as well as each outrigger. The outriggers are lowered during operation and leveled with the jacks to provide proper stability.

The top working surface of the trailer is coated with a durable, anti-slip coating to provide optimal operator safety.

The front section of the trailer is equipped with a covered, lockable storage area for tools and equipment.

Stang Industries

WWW.stangindustries.com

951-479-9810

Optional Equipment:

- Variety of inlet manifold connection types & sizes - Storz, Multi-lug, grooved, etc.
- Multiple inlet manifold - per customer requirements
- Electric monitor controls: tethered or wireless remote
- Park brake: hand-actuated
- Custom Colors Available
- Custom Flow Rates Available

Dimensional Information:

Width (Outriggers Stored): 90" (2287 mm)

Width (Outriggers Deployed): 142" (3594 mm)

Length (overall): 212" (5375 mm)

Height (for transport): 68" (1736 mm)

Deck height: 30" (762 mm)

Weight (maximum): 7500 lb (3402 kg)

Stang Industries

WWW.stangindustries.com

951-479-9810